



Article number:		5850-006	5834-009	5835-012	5806-005 (Charge xx/16)	5807-005 (Charge xx/16)	5808-005 (Charge xx/16)	5809-005 (Charge xx/16)	5866-007	5838-004
Voltage	V	220-240V	220-240V	220-240V	220-240	220-240	220-240	12	100-240	220-240
Frequenz	Hz	50/60	50	50	50	50	50	50	50/60	50
Input power:	W	6	9	11	5,5	5,5	5,5	5,5	7	4
lamp current	mA	48	75	91	46	46	46	690	67	40
Luminous flux	lm	806	806	1055	470	470	470	470	500	320
Bemessungslichtstrom:					390	390	390	390		
socket:		E27	E27	E27	GU10	E14	E27	GU5.3	E27	E27
dimensions - high:	mm	100	110	120	55	78	72,5	51,5	110	81
dimensions - diameter:	mm	60	60	60	50	50	50	50	60	45
colour temperature:	K	2700	2700	2700	3000	3000	3000	3000	3000	2700
Switching cycles:		15.000x	15.000x	15.000x	15.000x	15.000x	15.000x	15.000x	12.500x	15.000x
Warm-up time:	sec.	<1	<1	<1	<1	<1	<1	<1	<1	<1
Starting time:	sec.	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5	<0,5
Powerfactor:		0,53	0,51	0,53	0,523	0,523	0,523	0,673	0,51	
EEL		0,09	0,12	0,14	0,15	0,15	0,15	0,17	0,16	
Life time:	h	20.000	20000	20.000	20.000	20.000	20.000	20.000	20.000	15.000
CRI:	Ra	>80	>80	>80	>80	>80	>80	>80	>80	>80
Beam angle:	Grad				110	110	110	110	180	180
Mercury content:		0,00mg	0,00mg	0,00mg	0,00mg	0,00mg	0,00mg	0,00mg	0,00mg	0,00mg
Energy efficiency index: (Spectrum A++ until E)		A++	A+	A+	A+	A+	A+	A+	A+	A+
Dimmbar:		NO	NO	NO	NO	NO	NO	NO	YES	NO

**Article number:****5883-006**

Voltage	V	12
Frequenz	Hz	50
Input power:	W	6,5
lamp current	mA	780
Luminous flux	lm	470
Bemessungslichtstrom:		
socket:		GU5.3
dimensions - high:	mm	51
dimensions - diameter:	mm	49
colour temperature:	K	3000
Switching cycles:		10.000x
Warm-up time:	sec.	<1
Starting time:	sec.	<0,5
Powerfactor:		0,673
EEL		0,17
Life time:	h	25.000
CRI:	Ra	>90
Beam angle:	Grad	110
Mercury content:		0,00mg
Energy efficiency index: (Spectrum A++ until E)		A+
Dimmbar:		NO